

DK DVRs (4,8,16ch)

What is the 5brid?

5brid includes all types of Analog-HD cameras and IP. It supports the cameras of AHD, TVI, CVI, 960H & IP at the same time.

Frame rate table per resolution

Performance (Live, Rec.)	Camera	Camera resolution		
		960H	1.3M	2M
fps/ch	IP	15fps		
	TVI	30fps	30fps	15fps(4/16CH), 12fps(8CH)
	AHD			
	CVI			
	SD	30fps	-	-

Distinctive Features

Transcoding PB

Fast PB on Network

Digital Zoom

1X, 4X, 16X (3phase)

Network Access

Up to 32 User access

Push notification

Event Alarm

HDD Expansion

6-12TB

User covert

Independent

Network

DDNS, DHCP, UPnP

Multi-channel PB

SmartPhone viewer

S/W Full Package

Windows

VMS / RMS / Webviewer



MAC

Macviewer



Mobile Application

iPhone / iPad / Android



DVR WEB SERVICE

Includes all Sub-S/W

Digital Video Recorder

5brid C series (TVI, AHD, CVI, 960H & IP)

4CH | 8CH | 16CH

The most popular DVRs supporting 5 types of camera with FHD resolution



DK DVRs (4,8,16ch)



Feature

- 1 or 2 HDD Bays
- Multi-Language Supported
- Privacy Zone
- Covert Channel
- Watermarking
- DDNS, DHCP, UPnP

Distinctive Features

- Coaxitron
- P2P

General

- OS : Embedded Linux
- Compression : H.264
- Power Supply : 12V/2A, 12V/5A ~ Level 6
- Operating Temp : -10°C ~ 55°C
- Humidity : 10% ~ 90%
- Net Weight (w/o HDD) : 2.5Kg
- Certification : CE, FCC, RoHS Compliance

Network Software

- VMS, RMS
- Smartphone Viewer :




- Mac Viewer



Dimensions

4CH/8CH: 300x227x53

16CH: 378x340x50



Model Name		DK-2016C	DK-2008C	DX-2004C
System	OS	Embedded Linux - Built in flash memory		
	Language	Chinese, Chinese(S), Dutch, English, French, German, Hebrew, Hungari, Italian, Japanese, Korean, Latvian, Persian, Polish, Portuguese, Russian, Spanish, Sweden, Turkish, Arabic		
	Time Sync.	NTP, GMT, DST, Time Server		
	User	15 Users (Admin., User1 ~ User14)		
Camera	IP Camera	ONVIF Profile S		
Video	Input	16 BNC	8 BNC	4 BNC
	IPC Input	4 IPC	1 IPC	1 IPC
	Output	HDMI, VGA		
Audio	Input	16 RCA	8 RCA	4 RCA
	Output	1 HDMI, 1 RCA		
Video Recording	Speed	Max. 15fps/ch	Max. 12fps/ch	Max. 15fps/ch
	Resolution	Analog : 4MP/3MP/ 2MP/ 720P/ 960H IP : 4MP/ 3MP/ 2MP/ 720P		
	Mode	Auto, Continuous, Event		
	Event	Motion, Audio		
	Quality	5 Levels		
	Bit Rate	512Kbps ~ 3Mbps/Ch, Adjustable		
Audio Recording	Compression	G.711U		
	Audio Sampling Rate	8KHz		
	Audio Bit Rate	32Kbps		
Network	Interface	1 X Ethernet 10/100/1G		
	Compression	H.264		
	Speed	Max. 1080p 15fps/ch		
	Resolution	Max. 1080p		
Alarm	Post-Alarm	5sec / 5sec~5min		
	Motion Grid	32 x 24		
	Alarm Action	E-mail, Event Popup, Buzzer, Relay, PTZ Preset, Remote VMS, Front LED		
	Input / Output	4/1	4/1	4/1
Display	HDMI / VGA	Full HD, XGA		
	TV	SDTV(720x480)		
External Interface	PTZ / Keyboard	RS485 - Terminal Block		
Storage	Primary	2 HDD (Max. 6TB)	1 HDD (Max. 6TB)	
Main Features		UTC by Coax, Covert Channel, Digital Zoom(x1-x16), Watermarking		
		Two-way Audio, Detection/Search(Motion/Audio/Text)		
		e-mail (5 User with still image), Capture (1080p/VGA)		
Network Features	DDNS, DHCP, UPNP	Support		
	VMS, RMS	Windows		
	Smart Phone	Android, iPhone, iPad		
	Mac Viewer	Apple Mac OS		
General	Power Supply	12V / 2A		
	Consumption	24 WATTS		
	Operating Temp.	5~40 degree celcius		
	Humidity	10 ~ 90%		
	Weight w/o HDD	3kg	2.5kg	
	Dimension	378x340x50mm	300X227X53mm	
Certification	CE, FCC, RoHS Compliance			