

| | | |
|--------------------------------|---|--|
| Model | XVR-8204A-C1 (5 in 1 support AHD, TVI, CVI, Analog, IP Camera) 1080P Recording | |
| System | User Interface | Graphic User Interface (OSD) |
| | OS | Embedded Linux |
| | Operation Mode | preview, record, playback, backup, network |
| | Password Security | Multi-level user management |
| A/V Input | Video input | 4in, BNC |
| | Audio input | 4 in, RCA |
| A/V Output | HDMI output | Support |
| | VGA output | Support |
| | Display | 1, 4 |
| | Video standard | PAL/NTSC |
| | Loop | NO |
| | CVBS main output | 1 out, BNC; Resolution: PAL:704*576, NTSC: 704*480 |
| | Spot output | NO |
| | Audio output | 1 out,RCA |
| A/V encoding parameters | Video compression | H.264 |
| | Preview Resolution | 1080P:1920x1080,720P:1280x720,WD1:960x576,D1:704x576 |
| | Recording frame rate | 4CH 1080P :4*20fps |
| | Video frame rate | PAL: 1-25FPS NTSC:1-30FPS |
| | Video bit rate | WCIF(CIF):512-1024kbps,WD1(D1):1024-2048bps,720P:1536-3072Kbps,1080P:4608-6144Kbps |
| | Stream Type | Video & Audio/Video |
| | Audio compression | ADPCM |
| | Recording mode | Always/Schedule/Alarm recording/Motion detection recording |
| | Video search | Time/Channel/Event |
| | Audio bit rate | 8—32kbps |
| | Dual-stream | Supports |
| | Mobile phone Monitor | Supports Android phone/iPhone/iPad/Blackberry |
| | Recording resolution | 4CH AHD/TVI/CVI 1080P&4ch playback. 4CH IPC 1080P recording&4ch playback |
| | Playback | 1—4CH optional |
| HDD | Type | 1 piece SATA |
| | Maximum capacity | 6TB for each Sata connector |
| External connectors | Voice talk | NO |
| | Record mode | Audio & Video recording simultaneously |
| | Network protocol | Supports IE/PPPoE/DDNS/DHCP |
| | Domain name server | Support viewcan, 88110,reelink,3322, dyndns, no-ip, changeip, dnsexit domain name server as default value. |
| | Network | 1 RJ45 10M/100M |
| | Serial port | 1 RS-485 serial port |
| | E-SATA Connector | Supports |
| | USB Connector | 2 USB |
| | Firmware update | Support USB update/Network update |
| | Operation | -10℃-- +55℃ |
| | Operation Humidity | 10%--90% |
| | Power supply | 12V 2A |
| | Chassis | Standard 1.0U |
| | Dimension | 230mm (W)×315mm (D)×40mm (H) |
| | Weight(without HDD) | ≤1.5Kg |

