

Model	XVR-8208A-E1		
System	User Interface	Graphic User Interface (OSD)	
	OS	Embedded Linux	
	Operation Mode	preview, record, playback, backup, network	
	Password Security	Multi-level user management	
A/V Input	Video input	8in, BNC	
	Audio input	8 in, RCA	
A/V Output	HDMI output	Support	1024X768,1280X1024, 1366X768,1440X900, 720P, 1080P
	VGA output	Support	
	Display	1, 4, 6, 8,16	
	Video standard	PAL/NTSC	
	Loop	NO	
	CVBS main output	1 out, BNC; Resolution: PAL:704*576, NTSC: 704*480	
	Spot output	NO	
	Audio output	1 out,RCA	
A/V encoding parameters	Video compression	H.264	
	Display frame rate	PAL: 1-25FPS NTSC:1-30FPS	
	Recording frame rate	PAL: 1-25FPS NTSC:1-30FPS	
	Video frame rate	PAL: 1-25FPS NTSC:1-30FPS	
	Video bit rate	1080P:4608-6144kbps, 720P:1536kbps-3072kbps,WD1(D1):768-1536Kbps,WHd1(HD1):512-1280Kbps,WCF(CIF):384-768kbps,WQCF(CIF):192-384kbps	
	Stream Type	Video & Audio/Video	
	Audio compression	ADPCM	
	Recording mode	Always/Schedule/Alarm recording/Motion detection recording	
	Video search	Time/Channel/Event	
	Audio bit rate	8—32kbps	
	Dual-stream	Supports	
	Mobile phone Monitor	Supports Android phone/iPhone/iPad/Blackberry	
	Recording resolution	8ch AHD/TVI 1080P+8CH IPC 1080 recording&4ch playback , 16CH IPC 1080P recording&4ch playback	
	Playback	1—16CH optional	
HDD	Type	2 piece SATA	
	Maximum capacity	6TB for each Sata connector	
External connectors	Voice talk	NO	
	Record mode	Audio & Video recording simultaneously	
	Network protocol	Supports IE/PPPoE/DDNS/DHCP	
	Domain name server	Support viewcan,88110,reelink,3322, dyndns, no-ip, changeip, dnsexit domain name server as default	
	Network	1 RJ45 10M/100M	
	Serial port	1 RS-485 serial port	
	E-SATA Connector	Supports	
	USB Connector	2 USB	
	Firmware update	Support USB update/Network update	
	Alarm input	8ch in	
	Alarm output	1ch out	
Environment	Operation	-10℃-- +55℃	
	Operation Humidity	10%--90%	
	Power supply	12V 5A	
	Chassis	Standard 1.0U	
	Dimension	230mm (W)×315mm (D)×40mm (H)	
Weight(without HDD)	≤1.5kg		

