

Specifications

Models		NVR-8624A-E1
System	User Interface	Graphic User interface(OSD Menu)
	OS	Embedded Linux
	ONVIF	Support
	Security	Administrator; Different authority for users
Video	Video input	24 CH 1080P (by switch)
	Video output	CVBS/VGA/HDMI
	Display	1/4/6/8/9/10/13/16/24 optional
	VGA	1024*768,1280*1024,1440*900,1366*768,720P,1080P
	Video encoding resolution	2.0MP 1080P (1920X1080)
	Video frame rate	PAL: 1-25FPS NTSC:1-30FPS
Audio	Audio compress	ADPCM
	Audio in	IPC with audio
	Audio out	1 out RCA
Image & Storage	Video compress	H.264
	Image quality	1080P
	Sub stream	Sub stream1:VGA/QVGA; Sub stream2:720P (8FPS)
	Resolution	24CH 2.0MP recording & 8CH realtime playback;24CH 1080P recording&8CH 1080P playback; 8CH 2K/3MP/4MP recording + 4CH Playback
	Video Bit Rate	1080P:1536kbps-3072kbps;
	Audio Bit Rate	8—32Kbps
	Storage	2 HDD
Alarm	Alarm in/out	8 in/1 out
Others	Recording	Manual/alarm/motion detection/timing
	Network	RJ45 1000M Protocol: TCP/IP, PPPOE, SMTP,UPNP,DHCP,DDNS,RTSP
	Voice talk	Support
	Control Method	Remote control, USB mouse, panel control
	Mobile live view	I phone //IPAD/Android
	Domain name server	Support, www.viewcan.net ; 88110,reelink,3322, dyndns, no-ip, changeip, dnsexit domain name
	Backup	USB2.0, Network
	Serial	RS485
Power Supply	NVR	DC 12V 5A
	IPC	DC 12V 2A
Working Environment	Working temperature: -10℃~+60℃; Working humid:10%~ 90%	
Device Dimension	2HDD case:321mm(W)×405mm(D)×64mm(H)	
Weight	2HDD case:3KG	

