

7904 , 7908 , 7916

Key Features					
* H.264 high profile compression; * 3M/1080P/720P TVI or AHD or 960H hybrid input, auto-detect; * Supports dual stream; * Supports smart phone real time remotely monitoring, such as iPhone,Android; * Provide IE Activex,CMS,StreamView APP * Support P2P					
Specification:	DVR7904	DVR7908	DVR7916		
Main chipset	HI3520DV300				
	HI3521A				
	HI3531A				
	TP 2853C				
	16-bit True Color				
Operating System				Embedded Linux OS	
Password security				Multi-level users management, 1 Admin + 19 Users	
A/V Input	Video Input		3M/1080P/720P TVI or AHD or 960H camera*4	3M/1080P/720P TVI or AHD or 960H camera*8	3M/1080P/720P TVI or AHD or 960H camera*16
	Audio Input				1Ch RCA (Linear, 1kΩ)
A/V Output	VGA output				1024*768,1280*720,1280*800,1280*1024,1440*900,1920*1080(1080P)
	HDMI output				1024*768,1280*720,1280*800,1280*1024,1440*900,1920*1080(1080P)
	Audio output				1 RCA
A/V recording&playback parameters	Video compression				H.264 Baseline
	Video standard				PAL/NTSC
	Stream type				Video& Audio/Video
	Video recording rate		3M:P: 12fps/Ch; N:12fps/Ch 1080P:P: 15fps/Ch; N:15fps/Ch 720P: P:25fps/Ch; N:30fps/Ch 960H: P:25fps/Ch; N:30fps/Ch	3M:P: 8fps/Ch; N:8fps/Ch 1080P:P: 12fps/Ch; N:12fps/Ch 720P: P: 25fps/Ch; N:30fps/Ch 960H: P:25fps/Ch; N:30fps/Ch	3M:P: 12fps/Ch; N:12fps/Ch 1080P:P: 15fps/Ch; N:15fps/Ch 720P: P: 25fps/Ch; N:30fps/Ch 960H: P:25fps/Ch; N:30fps/Ch
	Video bit rate				384kbps-2048kbps@960H,1024kbps-4096kbps@720P,1024kbps-4096kbps@1080P,1024kbps-
	Dual Stream (Recording)				3M:2048x1536; 1080P:1920x1080; 720P:1280x720 ; 960H: 928x576(480)
	Resolution (Pixel)				Sub Stream (Network):3M/1080P/720P:Q720P; 960H:Q960H
	Record mode				Manual,Schedule,Motion
	Video search				Date/time, Event
	Display		1/4/SEQ	1/4/8/9/SEQ	1/4/8/9/16/SEQ
	Audio compression				16K*16bit AAC
	Audio bit rate				32Kbps
	playback channel		1Ch	4Ch	8Ch
	HDD	SATA Devices		1 x SATA HDD	1x SATA HDD
Maximum capacity		4TB	4TB	8TB	
External HDD		1 e-sata option	1 e-sata option	No	
External Interface	USB Connector				2 x USB2.0
	Serial Interface				1RS-485 serial port
	Alarm input/output				NO
	Network Interface		RJ 45,10M/100 M Ethernet	RJ 45,10M/100 M Ethernet	RJ 45,10M/100 M /1000M Ethernet
Network	Network protocol				TCP/IP, SMTP, HTTP, DHCP, PPPoE, NTP, DDNS,UPnP,FTP,RTSP,Onvif,P2P
	Mobile Device				iPhone, iPad,Android Phone, Android Pad
	System Upgrade				Supports USB update
	Remote Software				StreamView APP, IE Browser,Google Chrome Browser,Firefox Browser
General	Power Supply		Input 100~240V, Output 12V 2A	Input 100~240V, Output 12V 2A	Input 100~240V, Output 12V 3A
	Consumption				<10W without HDD
	Working temperature				-10℃~+55℃(14°F~131°F)
	Fan		No	1pcs	1pcs
	Working humidity				10%~90%
	Dimension (mm)		260(W) x 41(H) x 230(D)	260(W) x 41(H) x 230(D)	330(W) x 45(H) x 260(D)
	Weight (without hdd)		1.6kg	1.6kg	3kg

* Specification Subject to Change without Notice